



SIKTEMASKIN AS 200 TAP

The RETSCH AS 200 tap is suitable for dry sieving with test sieves of 200 mm or 8" diameter. The combination of horizontal, circular sieving motions with vertical taps reproduces the principle of hand sieving. The uniform mechanical action ensures reliable and reproducible measurement results.

This special type of sieving motion used by the AS 200 tap is specified in various standards for particle size analysis of materials such as activated carbon, diamonds, spices, metal powders, abrasives or cement. Operating the AS 200 tap is exceptionally easy and safe. The integrated clamping device allows for sieve stacks with up to 7 or 13 fractions, depending on the height of the sieve frame. The sieving time is set from 1 to 99 minutes via a digital display. The number of rotations and taps is fixed; the tapping motion can be deactivated, if required. A safety switch and an anti-trap protection provide maximum safety. Thanks to an integrated interface, the AS 200 tap can be controlled with the evaluation software EasySieve®.



ACCURACY & EFFICIENCY

- | Sieving with circular motion and vertical taps according to standards
- | Measuring range 20 µm to 25 mm
- | For 200 mm / 8" sieves
- | Sieve stack up to 350 mm
- | Digital time setting
- | Integrated interface
- | Suitable for dry sieving

SIKTEMASKIN AS 200 TAP

ACCESSORIES & OPTIONS

RETSCH sieve shakers can be equipped with a variety of accessories to meet a wide range of application requirements.



| Accessories for test sieves

Collecting pans, intermediate pans, intermediate rings and sieve lids.

| Sieving Aids

Chain rings, brushes, cubes, balls (e.g. for reducing agglomerations when sieving particles < 100 µm and keeping the mesh free).

| IQ/OQ Documents

We provide IQ/OQ documentation for the „control“ sieve shakers to support IQ/OQ certification by our customers.

| Sample Dividers

Meaningful results can only be obtained if the sample represents the original material. Sample dividers produce representative part samples, thus ensuring reproducibility of the analysis.

| Ultrasonic baths and dryers

Suitable for thorough cleaning of test sieves and for quick, gentle drying of samples and sieves.

RETSCH TEST SIEVES AND ACCESSORIES - ENGINEERED FOR SUPERIOR PERFORMANCE

PROGRAMVARE FOR EVALUERING – EASY SIEVE

EasySieve, the software for particle size analyses, exceeds manual evaluation in many aspects. The software is able to automatically control the necessary measurement and weighing procedures – from the registration of the weight of the sieve up to the evaluation of the data. It is simple and convenient to use and is also available in an FDA 21 CFR Part 11-conform version.



SIKTEMASKIN AS 200 TAP

TYPICAL SAMPLE MATERIALS

RETSCH's Analytical Sieve Shaker AS 200 tap is ideally suited for separation, fractioning and particle size determination of abrasives, charcoal, cement, coal, diamonds and spices.



sand



diamanter



coal



krydder

To find the best solution for your sample preparation task, visit our application database.

VIRKEMÅTE

AS 200 tap arbejder med en horisontalt roterende bevægelse av siktetårnet på 280 min-1. For å lette siktingen overføres omtrent som ved håndsikting bankeimpulser med frekvensen 150 min-1 via siktedekselet til siktetårnet. Vibrasjonene og bankeimpulsene er uavhengige av nettspenningen og sørger derfor for sammenlignbare sikterestultater uavhengig av hvor i verden siktingen er foretatt

SIKTEMASKIN AS 200 TAP

TECHNICAL DATA

funksjon	separering, fraksjonering, bestemmelse av partikkelstørrelse
bruksområde	biologi, byggematerialer, geologi / metallurgi, glass / keramikk, kjemi / plast, landbruk, maskinbygging / elektroteknikk, matvarer, medisin / legemidler, miljø / gjenvinning
matemateriale	pulver, massegoods
måleområde*	20 µm - 25 mm
bevegelse av siktematerialet	horisontalt kretsende bevegelse med bankeimpuls
maksimal ladning / siktemateriale	3 kg
maksimalt antall fraksjoner	7 / 13
maksimal vekt på siktematerialet	6 kg
turtall	280 min ⁻¹
bankeimpulser	150 min ⁻¹
tidsvisning	digital, 1 - 99 min
egnet for tørrsikting	ja
egnet for våtsikting	-
serielt brukergrensesnitt	ja
med testsertifikat / kan kalibreres	-
egnete siktediametre	200 mm / 203 mm (8")
maksimal høyde på siktematerialet	380 mm
kapslingstype	IP 40
Elektriske tilkoblingsdata	ulike spenninger
Nettilkobling	1-fase
kraftforbruk:	315 VA
b x h x d	700 x 640 x 450 mm / with sound enclosure cabinet: 700 x 670 x 520 mm
nettovekt	~ 68 kg / with sound enclosure cabinet: ~ 92 kg

*avhengig av matemateriale og apparatkonfigurering / apparatinnstillinger

[/as200tap](#)

BESTILLINGSINFO

TAP SIEVE SHAKER AS 200 TAP

Tap Sieve Shaker AS 200 tap for test sieves 200 mm / 203 mm (8") Ø, incl. sieve lid and EasySieve evaluation software (please order test sieves and collecting pan separately)

30.025.1001		AS 200 230 V, 50 Hz tap	incl. sound-enclosure cabinet, conforms with CE standards
-------------	---	-------------------------	---

30.025.0001		AS 200 230 V, 50 Hz tap
-------------	---	-------------------------

other electrical versions available for the same price

SIEVE STACKS AS 200 TAP

60.131.000998		Sieve stack consisting of 6 test sieves (ISO 3310-1), 200 mm Ø, 50 mm height (63 µm, 125 µm, 250 µm, 500 µm, 1 mm, 2 mm) and collecting pan
---------------	--	---

60.150.000998		Sieve stack consisting of 6 test sieves (ASTM E11), 203 mm (8") Ø, 50 mm (2") height (230 mesh, 120 mesh, 60 mesh, 35 mesh, 18 mesh, 10 mesh) and collecting pan
---------------	---	--

ADDITIONAL ITEMS AS 200 TAP

22.783.0001		Ball-pan hardness test kit acc. to ASTM D3802-79
-------------	---	--

99.200.0021	IQ/OQ Documentation for AS 200 tap		
-------------	------------------------------------	--	--

FOR TEST SIEVES 200 MM Ø, HEIGHT 50 MM

69.720.0050		Collecting pan	stainless steel	200 mm Ø	height 50 mm
-------------	---	----------------	-----------------	----------	--------------

FOR TEST SIEVES 200 MM Ø, HEIGHT 25 MM

69.720.0025		Collecting pan, stainless steel, 200 mm Ø, height 25 mm
-------------	---	---

FOR TEST SIEVES 203 MM Ø / 8" Ø, HEIGHT 2"

69.720.3050



Collecting pan, stainless steel, 8" Ø, height 2"

FOR TEST SIEVES 203 MM Ø / 8" Ø, HEIGHT 1"

69.720.3025



Collecting pan, stainless steel, 8" Ø, height 1"